






	STANDARDS	NATTÉ
COMPOSITION		100% Sunbrella® Acrylic
FINISH		Non PFAS, Water-Repellent & Stain-Proof
MINIMUM USEFUL WIDTH	EN 1773	140
WEIGHT	ISO 3801 g/sqm	290
ROLL LENGTH	LM	50
SPRAY TEST	ISO 4920 Class/5	5
COLOUR FASTNESS UV INDOOR	ISO 105 B02 Class/8	8
COLOUR FASTNESS TO WEATHER OUTDOOR	ISO 105 B04 1000 h Class/5	4-5
FLAME RETARDANCY		All these fabrics pass the following certifications: BS 5852-1 source 0, Cal 117, NFPA 260, EN 1021-1 (cigarette test)
CARE INSTRUCTIONS		     Ironing reinforces the treatment

All the values have a +/-5% tolerance



OPTIONAL FINISHES:



Also available on special order with a flame-retardant backing that passes the following certifications: BS 5852-1 source 1, EN1021-2 (match test), IMO FTP code part 8. Special order of 200 lm minimum per construction (with a possibility of mixing up to 4 colours). Increases fabric weight by 175 g/m².



Also available on special order with a waterproof backing that brings a waterproofness >1500 mm according to the schmerber test. Special order of 200 lm minimum per construction (with a possibility of mixing up to 4 colours). Increases fabric weight by 100 g/m².